

BÜFA® UD-Tape PP Flax 35

Prod.No. XXX

Product description BÜFA® UD PP Flax 35 is a flax fibre reinforced thermoplastic polypropylene tape with unidirectional fibre orientation. It is available in various widths and lengths.

Indicative values

Flax content	35	wt%
Density	1.18	g/cm ³
Thickness	0.22 - 0.25	mm
Areal weight	275	g/m ²
Tensile modulus 0°	9.2	GPa
Tensile strength 0°	70	MPa
Strain at break 0°	2	%
Melt temperature resin	163	°C

Storage /Handling This product must be stored at ambient temperatures, protected from sunlight and humidity. Shelf-life is not determined, we recommend to use within 12 months

Note: The Information given above is based on our current state of knowledge and experience. In view of the many factors that may influence working conditions and the application of our products, the user is not relieved from carrying out his own tests and experiments. No legally binding warranty of certain properties or suitability for a particular purpose can be derived from this information. It is the responsibility of the receiver or user of our products to observe proprietary rights as well as existing laws and regulations. The latest version of the corresponding EU Safety Data Sheet must also be observed.

BÜFA Thermoplastic Composites GmbH & Co. KG
Stubbenweg 40

26125 Oldenburg

GERMANY
Phone +49 441 9317905
thermoplasticcomposites@buefa.de
www.buefa.de
www.thermoplasticcomposites.de
A member of the BÜFA-Group